

# Lifeline **AUTO**



## **Lifeline AUTO Fully Automatic Defibrillator**

THE LATEST EVOLUTION IN THE AWARD-WINNING LIFELINE DEFIBRILLATOR SERIES

The Lifeline AUTO is a fully automatic defibrillator designed to analyze heart rhythms and automatically deliver a shock—without intervention—if needed.

The Lifeline AUTO includes all mission critical features necessary to provide the most advanced treatment for Sudden Cardiac Arrest. Yet it is so simple and unintimidating to use that even non-medical personnel can effectively save lives.

The Lifeline AUTO was developed by experienced multidisciplinary engineering teams and incorporates state-of-the-art digital signal processing techniques and advanced ECG analysis algorithms. The device

exceeds the American Heart Association performance recommendations—giving the user confidence the correct therapy is being delivered.

The Lifeline AUTO defibrillator uses advanced biphasic technology—including the most studied biphasic shock waveform—and automatically adjusts the shock delivery to the person's individual needs.

For first response professionals like police, fire, and EMS, the Lifeline AUTO is standard equipment. For schools, offices, malls, factories, and public places, it's becoming as vital as a fire extinguisher.

# Lifeline AUTO Fully Automatic Defibrillator

## TECHNICAL SPECIFICATIONS\*†

### DEFIBRILLATOR

#### TYPE

Fully Automatic external defibrillator

#### MODEL

DDU-120 SERIES

#### WAVEFORM

Biphasic Truncated Exponential  
(Impedance compensated)

#### ENERGY

Adult: 150 Joules  
Pediatric: 50 Joules  
(Nominal into 50 Ohm load)

#### CHARGE TIME\*

DBP-2800: Less than 6 seconds  
DBP-1400: Less than 9 seconds

#### VOICE PROMPTS

Extensive voice prompts guide user through operation of the unit

#### CONTROLS

Lighted On/Off button

#### INDICATORS

"check pads"  
"do not touch patient"  
"analyzing"  
armed-for-shock  
AED status LED

### DEFIBRILLATION/MONITORING PADS

#### MODEL

Adult – DDP-100  
Child/Infant – DDP-200P

#### TYPE

Pre-connected, single-use, non-polarized, disposable, self-adhesive electrodes with cable and connector

#### SURFACE AREA

103 cm<sup>2</sup> (nominal, each pad)  
50 cm<sup>2</sup> (nominal, each pad)

#### PAD PLACEMENT

Adult – Anterior/Anterior  
Child/Infant – Anterior/Posterior

#### CABLE LENGTH (typical)

48 in (122 cm)

### PATIENT ANALYSIS SYSTEM

#### PATIENT ANALYSIS

Automatically evaluates patient impedance for proper pad contact. Monitors signal quality and analyzes patient ECG for shockable/non-shockable rhythms

#### SENSITIVITY/SPECIFICITY

Meets AAMI-DF-39 specifications and AHA recommendations

### BATTERY PACK

MODEL DBP-2800**	MODEL DBP-1400**
<b>POWER</b> 15V, 2800 mAh	<b>POWER</b> 15V, 1400 mAh
<b>CAPACITY</b> 300 shocks or 16 hours continuous operation	<b>CAPACITY</b> 125 shocks or 8 hours continuous operation
<b>STANDBY LIFE</b> 7 years	<b>STANDBY LIFE</b> 5 years

#### TYPE

Lithium/Manganese Dioxide  
Disposable, recyclable, non-rechargeable

#### LOW BATTERY INDICATORS

Visible  
Audible

\*\*Typical, with new battery at 25° C

### SELF TESTS

#### AUTOMATIC

Automatic daily, weekly and monthly circuitry tests

#### BATTERY INSERTION

System integrity test on battery insertion

#### PAD PRESENCE

Pads preconnected tested daily

#### USER-INITIATED

Unit and battery pack system test may also be initiated by the user

#### STATUS INDICATION

Visual and audible indication of unit status

### EVENT DOCUMENTATION

#### INTERNAL EVENT RECORD

Critical ECG segments and rescue event parameters are recorded and can be downloaded to a removable data card

#### PC-BASED EVENT REVIEW

ECG with event tag display, and audio playback when available

#### REMOVABLE STORAGE (optional)

Up to 12 hours of ECG and event data storage (no audio option) or up to 2 hours of audio, ECG and event storage (audio option) on a removable data card. Actual length of storage is dependent on card capacity

### ENVIRONMENTAL

#### TEMPERATURE

Operating:  
0 to 50°C (32 to 122°F)  
Standby (with battery installed):  
0 to 50°C (32 to 122°F)

#### RELATIVE HUMIDITY

Operating / Standby: 5% – 95% (non-condensing)

#### ALTITUDE

-500 to 15,000 ft (-150 to 4500 m)  
per MIL-STD-810F 500.4 Procedure II

#### VIBRATION

Ground (MIL-STD-810F 514.5 Category 20)

Helicopter (RTCA/DO-160D, Section 8.8.2, Cat R, Zone 2, Curve G)

Jet Aircraft (RTCA/DO-160D, Section 8, Cat H, Zone 2, Curves B & R)

#### SHOCK/DROP ABUSE TOLERANCE

MIL-STD-810F 516.5 Procedure IV (1 meter, any edge, corner, or surface, in standby mode)

#### SEALING/WATER RESISTANCE

IEC60529 class IP54; Splash Proof, Dust Protected (Battery Pack installed)

#### ESD

EN 61000-4-2:2001, (open air up to 8kV or direct contact up to 6kV)

#### EMC (Emission)

EN 60601-1-2:1998 +A1:2002, limits EN 55011:1998 +A1:1999 +A2:2002 Group 1 Level B, method

#### EMC (Immunity)

EN 60601-2-4:2003, limits EN 61000-4-3:2002 Level 3 (10V/m), method

### PHYSICAL

#### SIZE

8.5 x 11.8 x 2.7 inches  
(22 x 30 x 7 cm)

#### WEIGHT (Approximate)

With DBP-1400: 4.2 lbs (1.9 kg)  
With DBP-2800: 4.4 lbs (2.0 kg)

\*Specifications subject to change without notice  
†Approved for sale within the European Economic Area